



## SITULA SPINDLE OILS

Tesla Situla are outstanding spindle oils that helps you gain an edge in the battle against maintenance and power costs. It reduces the rate of wear, eliminates spindle sticking, lowers power consumption and requirements, protects against corrosion and does not thicken during service.

Tesla Situla's antiwear properties permit it to carry greater loads than ordinary spindle oils, with reduced friction and lower power requirements.

Property:	Test Method:	Typical Values		
ISO Viscosity Grade	ISO 3448	10	22	15
Density @ 15°C , kg/m3	ASTM D4052	860	870	870
Kin.Viscosity Cst @ 40°C , mm2/s	ASTM D7042	10	22	15
Viscosity Index	ASTM D2270	95	95	95
Flash Point , deg C	ASTM D92 ,	150	160	170
Pour Point , deg C	ASTM D97	-12	-12	-12
P.Code		1701	1703	1702

Color Varies from Country to Country. Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. Advice and opinion noted herein are given in good faith and on the basis of the best information available, information is based on past history of the grade only and must not be construed as a guarantee of performance nor any legal liability is accepted by Tesla Corporation or any of its affiliates. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available with your nearest TESLA office or at [www.teslalube.com](http://www.teslalube.com). © Tesla Corporation, 2011

Product Nr: 1701-1703	Date Issued: 01-11-2011	Date Superseded:	Revision nr:
-----------------------	-------------------------	------------------	--------------

### TESLA TECHNOPRODUCTS FZE

(A Subsidiary of York & Boston LLC USA)

Dubai Office: PO BOX 114132, Dubai, UAE

Phone: 971(4) 455 1070: Fax (971) (4) 455 1071 Cell: (971)(50) 1144201

email: [info@teslalube.com](mailto:info@teslalube.com)