

TABIT 3000

Product Description

Tabit 3000 is a premium ashless 2-stroke lubricant developed for high powered water-cooled outboard engines fitted with oil-injection or premix systems and is formulated with the latest additive technology that helps in keeping the engine cleaner.

Tabit 3000 is easy to mix and forms stable mixtures with gasoline also at lower temperatures.

Tabit 3000 is suited for high powered 2-cycle water cooled outboard engines requiring an NMMA TC-W3® quality specification.

Specifications: Exceeds: NMMA TC-W3®

Property:	Test Method:	Typical Properties
SAE Grade		NA
Туре		Mineral
Cst @ 100°C	ASTM D7042 , mm2/s	6.9
Cst @ 40°C	ASTM D7042 , mm2/s	46
Viscosity Index	ASTM D2270	130
Flash Point	ASTM D92 , deg C	>96
Pour Point	ASTM D97 , deg C	-33
T.B.N	ASTM D 2896, mg KOH/g	3.45
Density, g/cc	D 4052	0.88

Color Varies from Country to Country. Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. Advice and opinion noted herein are given in good falth and on the basis of the best information available, information is based on past history of the grade only and must not be construed as a guarantee of performance nor any legal liability is accepted by Tesla Technoproducts or any of its affiliates. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available with your nearest TESLA office or at www.teslalube.com.© Tesla Technoproducts FZE, 2023

Product Nr: 1692 Date Issued: 01-10-2023 Date Superseded: Revision nr: 2

TESLA Techno Products FZE

(Under License and Technology from Tesla Corporation, USA)

PO BOX 114132, Dubai, UAE

Phone +971 56 1144201/+971 50 6402887/+91 98201 87007 email:

info@teslalube.com; info@jaykamal.com; www.teslalube.com