



CORSA PG COMPRESSOR OILS

Tesla CORSA PG compressor oils are premium quality fully synthetic oil, formulated from Poly Alkaline Glycols (PAG) and selected additives and is primarily recommended for compressor applications.

Tesla Corsa PG oils have anti-oxidants, anti-wear, and corrosion inhibitor additives enhance the performance of these products. They have ability to withstand dilution by hydro carbon gases, particularly suited for vacuum pump and centrifugal compressors handling hydrocarbon vapors. They can also function well as general purpose gear lubrication

These are soluble in water

Specifications met:

ISO Viscosity Grade	68	100	150
Density, g/cc, D 4052	1.05	1.05	1.05
Kin. Viscosity Cst at 40 ⁰ C, D 7042	68	100	150
Kin. Viscosity Cst at 100 ⁰ C, D 7042	14.4	20.5	27
Viscosity Index, D 2270	208	230	228
COC Flash, D 92, ⁰ C	227	227	266
Pour Point, D97, ⁰ C	-46	-44	-42
FZF pass Stage, Min, DIN 52354-2	12	12	12
P.Code	4508	4509	4510

Color Varies from Country to Country. Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. Advice and opinion noted herein are given in good faith and on the basis of the best information available, information is based on past history of the grade only and must not be construed as a guarantee of performance nor any legal liability is accepted by Tesla Corporation or any of its affiliates. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available with your nearest TESLA office or at www.teslalube.com. © Tesla Corporation, 2011

Product Nr: 4508-4510

Date Issued: 01-11-2011

Date Superseded:

Revision nr:

TESLA TECHNOPRODUCTS FZE

(A Subsidiary of York & Boston LLC USA)

Dubai Office: PO BOX 114132, Dubai, UAE

Phone: 971(4) 455 1070: Fax (971) (4) 455 1071 Cell: (971)(50) 1144201

email: info@teslalube.com