



TABIT 3000

Product Description:

Tabit 3000 is a premium ashless 2 stroke lubricant developed for high powered water cooled outboard engines fitted with oil-injection or premix systems and is formulated with the latest additive technology that helps in keeping the engine cleaner.

Tabit 3000 is easy to mix and forms stable mixtures with gasoline also at lower temperatures.

Tabit 3000 is suited for high powered 2 cycle water cooled outboard engines requiring NMMA 3 quality specifications

Specifications: Exceeds NMMA TC-W 3

Property:	Test Method:	Typical Values:	
SAE Viscosity Grade	SAE J300	20	
Density @ 15°C kg/m ³	ASTM D4052	0.88	
Kinematic Viscosity @ 40°C mm ² /s	ASTM D7042	39	
Kinematic Viscosity @ 100°C mm ² /s	ASTM D7042	6.9	
Viscosity Index	ASTM D2270	125	
Flash Point (COC) °C	ASTM D92	80	
Pour Point °C	ASTM D97	-21	
Total Base Number (TBN) mgKOH/g	ASTM D2896	8.9	
P.Code		1692	

Color Varies from Country to Country. Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. Advice and opinion noted herein are given in good faith and on the basis of the best information available, information is based on past history of the grade only and must not be construed as a guarantee of performance nor any legal liability is accepted by Tesla Corporation or any of its affiliates. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available with your nearest TESLA office or at www.teslalube.com © Tesla Corporation, 2011

Product Nr: 1692

Date Issued: 01-11-2011

Date Superseded:

Revision nr:

TESLA TECHNOPRODUCTS FZE

(A Subsidiary of York & Boston LLC USA)

Dubai Office: PO BOX 114132, Dubai, UAE

Phone: 971(4) 455 1070: Fax (971) (4) 455 1071 Cell: (971)(50) 1144201

email: info@teslalube.com